


Finalit No. 22

Cool Impregnation



- breathable and transparent protection
- resistant to UV-rays and de-icing salt
- resistant to acid rain and weather effects
- resistant to soiling and stains
- suitable for surfaces inside and outside

- premium impregnation
pH-value: n/a
- apply pure!
- 1L treats up to 100m², depending on the absorbency of the material



1) The product – Finalit No. 22 Cool Impregnation



a) Materials

Finalit No. 22 Cool Impregnation ist suitable for marble, granite, stoneware, ceramic, terracotta, brick, clinker, Solnhofener stone, limestone, sandstone, natural stone, aggro terrazzo, terrazzo and concrete.

Finalit No. 22 Cool Impregnation is not suitable for solvent-sensitive areas!

b) Characteristics

- does not contain wax, silicone or acrylate
- breathable (Goretex-effect): moisture can escape but cannot soak into the stone - very important for freshly laid floors
- no flaking or cracking
- pores / capillaries are not closed completely, penetrates the stone up to 5 mm, depending on the absorbency
- does not change the physical characteristics of the treated material
- breathability, color and water vapor permeability remain unchanged
- resistant to diluted alkalis or acids
- **IMPORTANT for samples:** thorough drying time: 24h, surface usable again after 1-2 hours

BEFORE STARTING TO WORK

- Take pictures of damages caused by daily cleaning and use of the premises, starting at the door, running clockwise.
- The bottom of wooden pieces of furniture (e.g. door frames) must be siliconed with transparent silicone, otherwise it may be damaged by water or detergent. Use special acid-resistant plastic tapes that do not cause adhesive residues!
- Switch off floor heating systems!

c) Application

Two possibilities for pre-treatment:

- apply Finalit No. 21 Fixative Penetrating Stopper (color enhancer) PURE on the clean and dry surface
- apply Finalit No. 21S Pores Filler (slight color enhancer on dark stones), diluted with water up to a 1:3 ratio, on the clean surface (can still be damp)



- temperature of the object has to be above +10°C
- surface to be treated has to be clean and dry
- apply Finalit No. 22 Cool Impregnation PURE and evenly for 1-2 times, depending on the absorbency of the material
- wipe off any excess immediatly (especially on polishes materials) by using terrycloth or streaks might appear

- alternative for large areas: use a single disc machine with a white pad and terrycloth beneath
- drying time: 1-2 hours, thorough drying time: 24 hours

It is absolutely essential that the treated surface is completely dry, otherwise Finalit No. 22 Cool Impregnation cannot work properly and develop the depot effect that is necessary for professional protection.

Recommendation for daily care:

Finalit No. 40 Citrus Scent Cleaner – pH neutral, suitable for all surfaces!

3) Specification

Appearance	Fluid, colorless
pH value	Not applicable
Packaging	0,25l, 0,5l, 1l, 5l, 20l tin cans
Storage	Protect from frost. Recommended shelf life: 1 year after opening.

4) Security regulations

The common precautions when handling chemicals must be observed. Ensure good ventilation/extraction at the workplace. Prevent formation of aerosols. Keep away from food, beverages and animal feed. Remove soiled and contaminated clothing immediately. Wash your hands before breaks and when work is finished. Avoid any contact with eyes and skin.

5) Note

This product information is based on careful laboratory tests and extensive practical experience. These are informal details. We recommend to determine whether the product meets the respective needs by sufficient testing. Our company shall not be held responsible for damages resulting from improper use of the product.