


# Finalit No. 7+

## Radical Graffiti and Paint Remover

- removes graffiti and residues of lacquer
- removes residues of adhesives and adhesive films, carpet adhesive or wallpaper glue
- removes nail polish and felt tip discolorations
- removes pencil discolorations
- removes epoxy resin and chewing gum

- pH-value: not applicable
- apply undiluted (pasty or liquid)
- 1kg cleans up to 10m<sup>2</sup>, depending on the degree of soiling
- free from chlorinated hydrocarbons, low in odor, highly effective, non-toxic, free of aromatics, does not affect metals



### 1) The product– Finalit No. 7+ Radical Graffiti and Paint Remover



#### a) Materials

For Granite, Sandstone, Natural stone, Marble, Solnhofener stone, Limestone, Terracotta, Clinker, Brick, Porcelain tile, Porcelain tiles, Terrazzo, Concrete. For natural and artificial stones except solvent sensitive materials (such as resin bonded industrial floors, plasters, paints, agglomerate marble, floors made of resin or Estrazzo).

**Attention!** Finalit No.7+ may have a caustic effect on polished soft stone. Sample tests recommended!

#### BEFORE STARTING TO WORK

- Take pictures of damages caused by daily cleaning and the use of the premises, starting at the door, running clockwise.
- The bottom of wooden pieces of furniture (e.g. door frames) must be siliconed with transparent silicone, otherwise it may be damaged by water or detergent. Use special acid-resistant plastic tapes that do not cause adhesive residues!
- Already existing coatings have to be removed completely with Finalit No. 5 Coating Remover or with a low-odor mixture of Finalit No. 1 Intensive Cleaner, No. 5 Coating Remover and No. 39 Compact (1:1:1) before working on the stain removal. Otherwise the cleaners cannot work effectively! Sometimes coatings are not visible. Perform tests with a) a blade („scrape“) or b) spill water - if the water drips off, the surface is coated.
- Switch off floor heating systems!

#### b) Application



- pre-clean surfaces that are soiled with graffiti or lacquer with Finalit No. 1 Intensive Cleaner
- exposure time: about 10 minutes
- rinse with water thoroughly
- warm up the surface that has to be treated (if possible)
- apply Finalit No. 7+ Radical Graffiti and Paint Remover by using a sponge, brush or scraper
- exposure time: 5-60 minutes, depending on intensity of soiling
- clean the surface with a high pressure cleaner or by water-sandblasting
- color residues: attach a compress to the surface and apply Finalit No. 12 Stain Killer, let set for 1-5 hours, depending on the intensity of discoloration - the stains will be bleached
- **neutralization:** clean the treated surface and the machinery that has been used during the cleaning process with Finalit No. 1 Intensive Cleaner (diluted with water at a 1:20 ratio)

**GENERAL NOTES:**

In exceptional cases it may be necessary to increase the exposure time or to apply Finalit No. 7+ Radical Graffiti and Paint Remover a second time.

For graffiti removal on painted/lacquered surfaces the maximum exposure time of Finalit No. 7+ is 30 seconds.

**2) Pro tips for Finalit No. 7+ Radical Graffiti and Paint Remover****a) Graffiti on sandstone or plaster**

In order to remove graffiti from coarse-pored materials (e.g. sand stone), it is recommend to use quartz sand 0.1-0.5 mm and a buffing machine with a brown pad first. Afterwards water-sandblast the surface with a high pressure cleaner (max. 150-180 bar) to remove color residues from the micro pores. Still remaining residues can be bleached with Finalit No. 12 Stain Killer as described above under „application - color residues“.

**b) Carpet and adhesive residues**

If a carpet is removed and natural stone or tiles are laid, the adhesive residues must be removed carefully. Apply Finalit No. 7+ Radical Graffiti and Paint Remover, let set overnight, remove the softened adhesive with a spatula.

Alternative: Spread quartz sand 0.1-2.0 mm on the surface and clean it with a single disc machine or brush grit 180 and water.

**c) Removal of chewing gum**

Remove chewing gum with a spatula, apply Finalit No. 7+ Radical Graffiti and Paint Remover, let set for about 30 minutes.

Residues can be removed by using quartz sand 0.1-2.0 mm, a single disc machine with a brown pad or a brush grit 180 or a high pressure cleaner.

**d) Epoxy resin - grouting residues**

Finalit No. 7+ removes epoxy resin residues. Apply the product (fluid) by spraying it on the surface, let set for about 30 minutes and remove the residues with quartz sand 0.1-2.0, a single disc machine with a brown pad or a brush grit 180 or a high pressure cleaner.

**d) Efflorescence from dispersion (polymer-modified adhesives / sealants)**

Stubborn residues from dispersion can be removed with Finalit No. 7+ or a mixture of Finalit No. 4 Yellow Stain Remover and Finalit No. 7+ Radical Graffiti and Paint Remover (1:1). Let set for about 20 minutes, rinse with water, then neutralize with Finalit No. 1 Intensive Cleaner (diluted at a 1:20 ratio). Remaining discolorations can be bleached with Finalit No. 12 Stain Killer or polished with Finalit No. 60 Grinding-/Polishing-Powder.

**3) Specification**

Appearance	pasty or fluid, whitish
pH value	not applicable
Packaging	0,25L, 1L, 5L, 1kg, 5kg plastic container
Storage	Protect from frost: Recommended shelf life: 1 year after opening.

**4) Security regulations**

The common precautions when handling chemicals must be observed. Ensure good ventilation/extraction at the workplace. Prevent formation of aerosols. Keep away from food, beverages and animal feed. Remove soiled and contaminated clothing immediately. Wash your hands before breaks and when work is finished. Avoid any contact with eyes and skin.

**5) Note**

This product information is based on careful laboratory tests and extensive practical experience. These are informal details. We recommend to determine whether the product meets the respective needs by sufficient testing. Our company shall not be held responsible for damages resulting from improper use of the product.